



DMA-Aero

EPSR2

Pressure and Vacuum Generator

- Vacuum to 0.2 inHg abs.
- Pressure to 103 inHg abs.
- 5000 hour pump guarantee
- Low maintenance
- Rack mount





DMA-Aero

EPSR2 Pressure and Vacuum Generator

FUNCTIONS

The DMA EPSR2 is a pressure and vacuum supply unit designed to generate the pneumatic supplies needed by Air Data Test Sets such as the MPS46 pressure controller. Housed in a 19 inch 3U high rack assembly it incorporates maintenance free diaphragm pumps.

The EPSR2 contains three membrane pumps, two for vacuum and one for pressure. These pumps are controlled by a dedicated internal microprocessor that schedules the operation of the pumps to achieve the desired pressures and vacuums. Vacuum pumps will operate either in parallel or series dependant on the ultimate flow rate and vacuum desired. The pumps feed internal storage volumes that are monitored by sensors to ensure vacuum and pressure values are as required and maximum and minimum values are not exceeded. When maximum values are reached the pumps are turned off. LED indicators on the front panel indicate when the pressure and vacuum values are reached. A front panel control button enables the absolute vacuum possible to be demanded but equally ensures that the pumps are not excessively overloaded. A front panel mounted drain valve is also provided for any internal moisture release. A wide range capability power supply is provided.

The EPSR2 enables pressures equivalent to 1,000 knots airspeed to be achieved, and vacuums equivalent to altitudes of 110,000 feet. The flow rates ensure that high rates of change, ft/minute and knots/minute can be maintained into both large and small volumes.

Two pneumatic fittings with AN modified couplings connect the EPSR2 generator with the DMA MPS46 air data tester. A cable connects the MPS46 and EPSR2 to enable control of the pumps by the ADTS. By simply connecting the ADTS with the EPSR2 pressure generator, then connecting the power supply, when the unit is turned On the system is operational.

LOW MAINTENANCE

The membrane pumps utilized do not require any maintenance. It is only necessary to periodically drain (every 1 to 3 months depending on the use) the over-pressure reservoir by pressing the drain button for 5 seconds.

SPECIFICATIONS

Pressure maximum 103 inHg (3500 hPa) - 1,000 knots equivalent

Vacuum maximum 0.2 inHg (7 hPa) – 110,000 feet equivalent

Flow capability (vacuum):

@ 10,000 ft into 145 cu in (2.4 litres) will achieve 36,000 ft/min

@ 50,000 ft into 145 cu in (2.4 litres) will achieve 15,800 ft/min

@ 110,000 ft into 145 cu in (2.4 litres) will achieve 1,100 ft/min

Flow capability (pressure):

@ 44 inHg into 145 cu in (2.4 litres) will achieve 44 inHg/min

@ 77 inHg into 145 cu in (2.4 litres) will achieve 42 inHg/min

@ 106 inHg into 145 cu in (2.4 litres) will achieve 38 inHg/min

PHYSICAL SPECIFICATIONS

Weight: 24 lb (11 kg)

Dimensions: L 17 x W 14 x H 5.25 in
(440 x 360 x 133 mm)

POWER SUPPLY

Universal power supply: 90-240 Vac; 50-400 Hz.

TEMPERATURE RANGE

Operating: -5°C to +50°C

Storage: -20°C to +70°C

CONNECTIONS

All rear panel mounted

AN fittings with O ring seals for finger tight operation.

WARRANTY

Unit: 24 months

Pumps: 5,000 hours

OPTIONS

Custom Pitot/Static connections available.

Interconnecting cable for remote control via MPS46 available.

A flight-line cased version, the EPS1 is available.



Ongoing development results in specifications being subject to change without notice



DMA-Aero

11 Old Sugar Hollow Road
Danbury, CT 06812

Tel: 203 790-8371

Fax: 203 743-2051

E-mail: sales@dma-aero.com

Web: www.dma-aero.com

Representative